

STANDARD SPECIFICATIONS

Plates: Formed 1/8" steel plates. Model BPA & BPB have angle stiffeners located on 12" centers and on both ends. Models BPC & BPD are made in nominal 12" length increments with 1-1/4" channel flange.

Ball Transfer: 50 lbs. capacity, 1" dia. ball transfer with 1/4" - 20 unc stud mount. Hardened ball cup, zinc plated protective cover provides low torque and extended life.

Sizes: See chart near related model for standard sizes.

MODEL BPA & BPAS:

Designed to be placed on an existing work table, cart, etc. Available in widths from 12" to 50" and in lengths from 12" to 120", by 1.00" increments.



STANDARD STRAIGHT SECTION			STANDARD STAGGERED SECTION			
SIZE INCHES	3" CENTERS MODELS BPA_	4" CENTERS MODELS BPA_	6" CENTERS MODELS BPA_	3" CENTERS MODELS BPAS_	4" CENTERS MODELS BPAS_	6" CENTERS MODELS BPAS_
24 X 24	BPA-24-24-3	BPA-24-24-4	BPA-24-24-6	BPAS-24-24-4	BPAS-24-24-6	BPAS-24-24-3
24 X 36	BPA-24-36-3	BPA-24-36-4	BPA-24-36-6	BPAS-24-36-6	BPAS-24-36-3	BPAS-24-36-4
24 X 48	BPA-24-48-3	BPA-24-48-4	BPA-24-48-6	BPAS-24-48-3	BPAS-24-48-4	BPAS-24-48-6
36 X 36	BPA-36-36-3	BPA-36-36-4	BPA-36-36-6	BPAS-36-36-4	BPAS-36-36-6	BPAS-36-36-3
36 X 48	BPA-36-48-3	BPA-36-48-4	BPA-36-48-6	BPAS-36-48-6	BPAS-36-48-3	BPAS-36-48-4
48 X 48	BPA-48-48-3	BPA-48-48-4	BPA-48-48-6	BPAS-48-48-3	BPAS-48-48-4	BPAS-48-48-6

